

CANvu™ 355

3.5" Colour Screen Display



Technical Data



Introduction

The CANvu 355 has a 3.5inch colour display with fully integrated input and output features. One of our most popular displays it is available in 4 variants with Low Profile and reduced I/O combinations. The display is part of the family of compact, flexible, and rugged CAN bus monitors from CANtronik.

With 7 analogue inputs, 4 relay outputs combined with 3 digital inputs, 2 CAN input connections, plus a USB port the CANvu 355 allows maximum functionality.

The QVGA colour display can be viewed in full sunlight, and the unit is totally sealed and electronically extremely durable. The display can provide system control functions, alarm functionality, and has configurable data logging capability. It is equipped to meet the challenge of providing tough, flexible, maintenance free instrumentation in even the very harshest of environments.

Key Features

- 2 x CANbus, 1 x RS232 Connection
- 7 x Analogue & 3 Digital Inputs
- 4 x Relay Outputs
- Data Logging & Control Capability
- Wi-Fi Telematics Compatible
- Ruggedised Display
- J1939/NMEA 2000/Tier 4 Support
- IP66 Front & IP67 Rear

ADDRESS

Hindle Controls, Caledonis Street,
Bradford, West Yorkshire, BD5 0EL



0044 (0) 1274 727234



controls@hindle.co.uk



CANvu™ 355

3.5" Colour Screen Display

Reliability

CANvu products continue to be successfully deployed in an enormously diverse range of applications where total reliability is vital.

All products, bespoke or standard range are backed up by a dedicated central team of specialist engineers able to rapidly adapt any product for a specific application and to provide an unrivalled level of customer support.

The CANvu displays are also supported with a return to base extended 24-month Manufacture warranty against mechanical failure or material defects.

Software

Our SDK is offered for a one-off licence fee from which customers can develop their own bespoke application solution. Available are optional plugins for CANopen, J1939, NMEA 2000, and support hours are included should your engineers need any help along the way.

Alternatively, CANtronik can develop bespoke software to your specification using our experienced in house engineers.

Over the years our engineers have developed software for our displays to run rock crushers & mining machinery, measure performance of spraying equipment, acting as battery monitors, boat gyro stabilisers, plus many more including military and aerospace applications.

Also available is our CANvu™ Engine Monitor standard software for Industrial and Marine, which can be pre-loaded to our displays receiving and displaying J1939 engine and transmission data, including common Tier4 parameters, with active alarms (from DM1) & NMEA 2000 data, where supported.

Accessories

- Cable Harnesses
- Protective Sun Covers

- Mounting Kits
- Branding - Labels & Boxes

ADDRESS

Hindle Controls, Caledonis Street,
Bradford, West Yorkshire, BD5 0EL



0044 (0) 1274 727234



controls@hindle.co.uk



CANvu™ 355

3.5" Colour Screen Display

Specifications

| Hardware | |
|-----------------------|--|
| CPU | Processor is Freescale iMX 286, running 454 MHz |
| Flash Memory | 128 MB NAND |
| SDRAM | 128 MB |
| Electrical | |
| Display | a-Si TFT LCD 3.5" |
| Resolution | 320 (H) x 240 (V) QVGA |
| Active Area | 70.08mm (H) x 52.56mm (V) |
| Viewing Angle | 130/110 degrees from 6 O'clock |
| Number of Colours | 64K |
| Contrast Ratio | 300:1 |
| Brightness | 750 NIT |
| Power Requirements | 10V to 32V DC |
| Sounder | Internal Buzzer |
| Connection | (2) 12 Pin Deutsch DT04-12PA Moulded in Receptacle |
| Communications | 1 X RS232, 2 X CAN Bus 2.0B (1 isolated), USB2.0 |
| Environmental | |
| Operating Temperature | -40 to +70 Degrees Celsius |
| Storage Temperature | -40 to +80 Degrees Celsius |
| Degree of Protection | IP 66 front IP 67 back |
| Mechanical | |
| Case Material | ABS |
| Case Colour | Black |
| Dimensions | 95mm (W) x 95mm (H) x 23mm forward and 23mm rear (D) |
| Part Number | |
| 900355 | CANvu™ 355 - 3.5" Colour Screen Display |

ADDRESS

Hindle Controls, Caledonis Street,
Bradford, West Yorkshire, BD5 0EL



0044 (0) 1274 727234




controls@hindle.co.uk



CANvu™ 355

3.5" Colour Screen Display

Dimensions



Connectors

| Primary | | Secondary | |
|---------|-----------------------------|-----------|-----------------------------|
| 1 | Ground | 1 | Sensor 1 Analog Input |
| 2 | Ground & Power ¹ | 2 | Sensor 2 Analog Input |
| 3 | Relay/Solenoid Output 1 | 3 | Sensor 3 Analog Input |
| 4 | Relay/Solenoid Output 2 | 4 | Sensor 4 Analog Input |
| 5 | Isolated CAN Supply (-) | 5 | Sensor 5 Analog Input |
| 6 | Isolated CAN Supply (+) | 6 | Sensor 6 Analog Input |
| 7 | Isolated CAN Data H | 7 | Sensor 7 Analog Input |
| 8 | Isolated CAN Data L | 8 | Digital Input/Flow Sensor 1 |
| 9 | Relay/Solenoid Output 3 | 9 | Digital Input/Flow Sensor 2 |
| 10 | Relay/Solenoid Output 4 | 10 | Tachometer Input |
| 11 | Primary CAN Data L | 11 | RS232 Receiver |
| 12 | Primary CAN Data H | 12 | RS232 Transmit |

Note 1. (10-32V DC) Supply should be protected by 1A – Rated circuit breaker/ fuse.

IMPORTANT NOTICE

Safety Warning: Please note analogue input voltages should not exceed the supply voltage or damage may occur. No power should be present on the harness during connection. USB port should not be used for charging external equipment such as mobile phones.

Connect Harness 1 (Primary) noting correct orientation of connector. Ensure it is fully mated so the connector latches into place. Then connect Harness 2 (Secondary) note correct orientation of connector. Ensure it is fully mated so the connector latches into place.

ADDRESS

Hindle Controls, Caledonis Street,
Bradford, West Yorkshire, BD5 0EL



0044 (0) 1274 727234



controls@hindle.co.uk

